

INDUCTION GOLD / SILVER MELTING FURNACE

FEATURES	MODEL BT-02
HEATING TYPE	INDUCTION
HEATING POWER	4 KW
CRUCIBLE CAPACITY	3 KG (150cm ³)
THERMOCOUPLE	K TYPE
PNEUMATIC LIFT	TO LIFT CRUCIBLE
MAXIMUM TEMPERATURE	1100° C
INDUCTION POWER REGULATOR	YES
DISPLAY	LCD
TEMPERATURE CONTROL	PID WITH TARGET SET CONTROL
BASE	BASE TO KEEP HOT CRUCIBLE
COOLING	WATER CIRCULATION
INPUT	220V 50Hz 1 Ph



WAX BURNOUT FURNACE

FEATURES	MODEL BT 800
CONTROL	PID TEMPERATURE CONTROL
No. OF PROGRAMS	2 PROGRAM 16 STEP EACH
MAXIMUM TEMPERATURE	800° C
THERMOCOUPLE	K TYPE
HEATING ELEMENT	MOLYBDENUM 8 ELEMENTS
THERMAL INSULATION	ALUMINOSILICATE
WAX COLLECTION TRAY	STEEL
DISPLAY	LCD
TEMPERATURE CONTROL	STEP PROGRAM CONTROL
CHAMBER DIMENSIONS (mm)	400 (W) X 450 (D) X 270 (H)
No. OF FLASKS WITHOUT FLANGE	9 FLASKS (4" DIA) / 16 FLASKS (3" DIA)
INPUT	220V 50Hz 1 Ph 2.4KW



MAGNETIC GOLD / SILVER POLISHER

FEATURES	MODEL MP 1000
CAPACITY	1000 G OF JEWELLERY
MOTOR POWER	750 W
MAXIMUM SPEED	2400 RPM
ROTATION	CLOCKWISE & ANTI CLOCKWISE
SET TIMING FORWARD & REVERSE	1 MINUTES TO 9 HOURS ADJUSTABLE
CONTAINER	PLASTIC
MEDIA	STAINLESS STEEL PINS 0.3 X 5 mm
No. OF PROGRAM	1
DISPLAY	8 SEGMENT LED
MEDIA REMOVER	MAGNETIC STICK INCLUDED
SAFETY SWITCH	OVERLOAD PROTECTION
INPUT	220V 50Hz 1 Ph 2.4KW



CONTACTS

MIDDLE EAST

BIJOUX TEC
ADVANCED JEWELLERY AUTOMATION

BIJOUXTEC DMCC
P.O.BOX 57975
D5, G/F, GEMPLEX 1, DMCC
DUBAI, UNITED ARAB EMIRATES
TEL : +971 (4) 434-3695 FAX: +971 (4) 434-3694
sales@bijouxtec.com

UAE



DIAMOND GENERAL TRADING

DIAMOND GENERAL TRADING
P.O.BOX No. 57976,
GOLD SOUK, DEIRA,
DUBAI, UAE
TEL / FAX : +971 (4) 2260106
dgt@bijouxtec.com